

Data Sheet

OPAMP 4MHZ HIGHVOLT 8CAN MIL HT SUSA CODE:8542330000

Manufacturers Renesas Technology Corp

Package/Case 8-Pin Metal Can

Product Type Amplifier ICs

RoHS

Lifecycle



Images are for reference only

Please submit RFQ for HA2-2640-2 or Email to us; sales@ovaga.com We will contact you in 12 hours.

RFO

General Description

HA-2640 and HA-2645 are monolithic operational amplifiers which are designed to deliver unprecedented dynamic specifications for a high voltage internally compensated device. These dielectrically isolated devices offer very low values for offset voltage and offset current coupled with large output voltage swing and common mode input voltage. For maximum reliability, these amplifiers offer unconditional output overload protection through current limiting and a chip temperature sensing circuit. This sensing device turns the amplifier "off", when the chip reaches a certain temperature level. These amplifiers deliver ± 35 V common mode input voltage range, ± 35 V output voltage swing, and up to ± 40 V supply range for use in such designs as regulators, power supplies, and industrial control systems. 4MHz gain bandwidth and 5V/µs slew rate make these devices excellent components for high performance signal conditioning applications. Outstanding input and output voltage swings coupled with a low 5nA offset current make these amplifiers excitation designs.

Features

Output Voltage Swing ±35V

Supply Voltage $\pm 10V$ to $\pm 40V$

Offset Current 5nA

Bandwidth 4MHz

Slew Rate 5V/µs

Common Mode Input Voltage Range ±35V

Output Overload Protection



Related Products



HA17358B Renesas Technology Corp DIP-8



HA1-5104-2
Renesas Technology Corp
DIP-14



HA2-5002-2 Renesas Technology Corp 8-Pin Metal Can



HA2-2620-2
Renesas Technology Corp
8-Pin Metal Can



HA7-5147-2 Renesas Technology Corp CDIP-8



HA7-5102-2
Renesas Technology Corp
CDIP-8



HA7-2640-2 Renesas Technology Corp CDIP-8



HA2-2520-2
Renesas Technology Corp
8-Pin Metal Can