

LM324ADTBG

Data Sheet

3-32V Quad Operational Amplifier with 3mV VIO - Pb-Free; Package: TSSOP-14; No of Pins: 14; Container: Tube; Qty per Container: 96,Op Amps 3-32V Quad 3mV VIO Commercial Temp

Manufacturers ON Semiconductor, LLC

Package/Case TSSOP-14

Product Type Amplifier ICs

RoHS Green

Lifecycle



Images are for reference only

Please submit RFQ for LM324ADTBG or <u>Emailto:sales@ovaga.com</u> We will contact you in 12 hours.

<u>RFQ</u>

General Description

These devices consist of four independent high-gain frequency-compensated operational amplifiers that are designed specifically to operate from a single supply or split supply over a wide range of voltages.

Features Application

2-kV ESD Protection for:

ONSEMI

LM224K, LM224KA

LM324K, LM324KA

LM2902K, LM2902KV, LM2902KAV

Wide Supply Ranges

Single Supply: 3 V to 32 V

Dual Supplies: $\pm 1.5 \text{ V}$ to $\pm 16 \text{ V}$

Low Supply-Current Drain Independent of

Supply Voltage: 0.8 mA Typical

Common-Mode Input Voltage Range Includes

Ground, Allowing Direct Sensing Near Ground

Low Input Bias and Offset Parameters

Input Offset Voltage: 3 mV Typical

A Versions: 2 mV Typical

Input Offset Current: 2 nA Typical

Input Bias Current: 20 nA Typical

A Versions: 15 nA Typical

Differential Input Voltage Range Equal to

Maximum-Rated Supply Voltage:

32 V (26 V for LM2902)

Open-Loop Differential Voltage Amplification:

100 V/mV Typical

Internal Frequency Compensation

On Products Compliant to MIL-PRF-38535,

All Parameters are Tested Unless Otherwise

Noted. On All Other Products, Production

Processing Does Not Necessarily Include Testing

of All Parameters.

Related Products



LM324ADG
ON Semiconductor, LLC
SOIC-14



LM2904VDR2G
ON Semiconductor, LLC
SOIC-8



LM321SN3T1G

ON Semiconductor, LLC
SOT23-5



LM224DR2G
ON Semiconductor, LLC
SOIC-14



LM2904VDG

ON Semiconductor, LLC

SOIC-8

a) ovaga

ON Semiconductor, LLC MSOP-8

LM2904DMR2



LM833NG

ON Semiconductor, LLC 8-PDIP



LM358NG

ON Semiconductor, LLC PDIP-8