

## LM2903DR2

Data Sheet

Comparator ICs 2-36v dual

Manufacturers	ON Semiconductor, LLC	E E E
Package/Case	SOIC-8	
Product Type	Comparator ICs	EEEE
RoHS		
Lifecycle		Images are for reference only
Please submit RFQ fo	or LM2903DR2 or <u>Email to us: sales@ovaga.com</u> We will contact you	in 12 hours. <u>RFQ</u>

#### **General Description**

The LM393B and LM2903B devices are the next generation versions of the industry-standardLM393 and LM2903 comparator family. These next generation devices provide outstanding value forcost-sensitive applications, with features including lower offset voltage, higher supply voltagecapability, lower supply current, lower input bias current, lower propagation delay, and improved2kV ESD performance with drop-in replacement convenience.

All devices consist of two independent voltage comparators that are designed to operate from a single power supply over a wide range of voltages. Operation from dual supplies also ispossible as long as the difference between the two supplies is within 2 V to 36 V, and VCC is at least 1.5 V more positive than the input common-mode voltage. Current drain is independent of the supply voltage. The outputs can be connected to other open-collector outputs to achieve wired-AND relationships.

#### Features


Single-Supply or Dual Supplies

- Wide range of supplyvoltage
- Maximum rating: 2 V to 36 V
- Tested to 30 V:non-V devices
- Tested to 32 V: V-suffix devices
- Tested to 36V: B-suffix devices
- Low supply-current drain independent of supply voltage: 0.2 mA (typical) percomparator
- Low input bias current: 15 nA (typical, 'B' device)
- Low lurrent: 2 nA (Typical)
- Low input offset voltage: 0.37 mV (typical, 'B' device)
- Common-mode input voltage range
- Includes Ground
- Differential input voltage range equal to maximum-rated supply voltage: ±36V
- Low output saturation voltage
- Output compatible with TTL, MOS, and CMOS

#### **Related Products**



#### LM311DR2G



Micro8



LMV393DMR2G ON Semiconductor, LLC



LM2901VDR2G ON Semiconductor, LLC SOIC-14




#### LM211DR2G

**LM311DG** 

ON Semiconductor, LLC SOIC-8

# E E E E



#### LMV393MUTAG

ON Semiconductor, LLC UDFN-8

### Application

ONSEMI



#### **LM311NG**

ON Semiconductor, LLC

PDIP-8



LM211DG ON Semiconductor, LLC

SOIC-8