

+3.3 V/+5 V, Low Power, Quad 12-Bit CMOS DAC; Package: SOIC - Wide; No of Pins: 28; Temperature Range: Commercial

Manufacturers	Analog Devices, Inc
Package/Case	SOIC-28
Product Type	Data Conversion ICs
RoHS	Rohs
Lifecycle	



Images are for reference only

Please submit RFQ for AD7564ARZ-B or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

General Description

The AD7564 contains four 12-bit DACs in one monolithic device. The DACs are standard current output with separate VREF , IOUT1 , IOUT2 and RFB terminals. These DACs operate from a single +3.3 V to +5 V supply.

The AD7564 is a serial input device. Data is loaded using FSIN, CLKIN and SDIN. Two address pins A0 and A1 set up a device address, and this feature may be used to simplify device loading in a multi-DAC environment. Alternatively, A0 and A1 can be ignored and the serial out capability used to configure a daisy-chained system. All DACs can be simultaneously updated using the asynchronous LDAC input, and they can be cleared by asserting the asynchronous CLR input.

The device is packaged in 28-pin SOIC, SSOP and DIP packages.

Features

Four 12-Bit DACs in One Package

4-Quadrant Multiplication

Separate References

Single Supply Operation

Guaranteed Specifications with +3.3V/+5 Supply

Low Power

Versatile Serial Interface

Simultaneous Update Capability

Reset Function

28-Pin SOIC, SSOP and DIP Packages

Application

Process control

Portable instrumentation

General purpose test equipment



Related Products



[ADAS3022BCPZ](#)

Analog Devices, Inc
LFCSP-40




[AD574AJNZ](#)

Analog Devices, Inc
PDIP-28



[AD7938BSUZ](#)

Analog Devices, Inc
TQFP-32



[AD7266BSUZ](#)

Analog Devices, Inc
TQFP-32



[AD7401YRWZ](#)

Analog Devices, Inc
SOIC-16



[AD7192BRUZ-REEL](#)

Analog Devices, Inc
TSSOP-24



[AD7124-8BCPZ-RL7](#)

Analog Devices, Inc

LFCSP-32



[AD9680BCPZ-500](#)

Analog Devices, Inc

LFCSP-64