


Analog Multiplexer Dual 4:1 Automotive 16-Pin TSSOP T/R

Manufacturers	Analog Devices, Inc
Package/Case	TSSOP-16
Product Type	Multiplexer Switch ICs
RoHS	Rohs
Lifecycle	



Images are for reference only

Please submit RFQ for ADG659YRUZ-REEL7 or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

General Description

The ADG658 and ADG659 are low voltage, CMOS analog multiplexers comprised of eight single channels and four differential channels, respectively. The ADG658 switches one of eight inputs (S1–S8) to a common output, D, as determined by the 3-bit binary address lines A0, A1, and A2. The ADG659 switches one of four differential inputs to a common differential output, as determined by the 2-bit binary address lines A0 and A1. An EN input on both devices enables or disables the device. When disabled, all channels are switched off.

These devices are designed on an enhanced process that provides lower power dissipation yet gives high switching speeds. These devices can operate equally well as either multiplexers or demultiplexers and have an input range that extends to the supplies. All channels exhibit break-before-make switching action, preventing momentary shorting when switching channels. All digital inputs have 0.8 V to 2.4 V logic thresholds, ensuring TTL/CMOS logic compatibility when using single +5 V or dual ±5 V supplies.

The ADG658 and ADG659 are available in 16-lead TSSOP/QSOP packages and 16-lead 4 mm × 4 mm LFCSP packages.

Product Highlights

Single- and dual-supply operation. The ADG658 and ADG659 offer high performance and are fully specified and guaranteed with ±5 V, +5 V, and +3 V supply rails.

Automotive temperature range –40°C to +125°C.

Low power consumption, typically <0.1 μW.

16-lead 4 mm × 4 mm LFCSP packages, 16-lead TSSOP package and 16-lead QSOP package.

Features

2 V to 12 V single supply

Automotive temperature range -40°C to $+125^{\circ}\text{C}$

45 Ω on resistance over full signal range

Rail-to-rail switching operation

Differential 4-to-1 multiplexer

16-lead LFCSP/TSSOP/QSOP packages

Typical power consumption $<0.1 \mu\text{W}$

TTL/CMOS compatible inputs

Package upgrades to 74HC4051 / 74HC4052 and MAX4051 / MAX4052 / MAX4581 / MAX4582

Application

Automotive applications

Automatic test equipment

Data acquisition systems

Battery-powered systems



Communication systems

Audio and video signal routing


Relay replacement

Sample-and-hold systems

Industrial control systems



Related Products



[ADV7181CBSTZ](#)

Analog Devices, Inc
LQFP-64



[AD8170AR](#)

Analog Devices, Inc
SOP8



[AD724JR](#)

Analog Devices, Inc
SOIC-16



[ADV7393BCPZ](#)

Analog Devices, Inc
LFCSP-VQ-40



[ADV7391WBCPZ](#)

Analog Devices, Inc
LFSCP-3




[ADV7390BCPZ](#)

Analog Devices, Inc
QFN32



[ADV7341BSTZ](#)

Analog Devices, Inc
LQFP-64



[ADUM4160BRIZ](#)

Analog Devices, Inc
SOIC-16