

LTM4637IV#PBF

Data Sheet

IC REG BUCK ADJ 20A 133LGA

Manufacturers	Analog Devices, Inc		
Package/Case	133-LGA	S STATES	
Product Type	Power Management ICs		
RoHS			
Lifecycle		Images are for reference only	
Please submit RFQ for LTM4637IV#PBF or Email to us: sales@ovaga.com We will contact you in 12 hours.			

General Description

The LTM4637 is a complete 20A output high efficiency switch mode step-down DC/DC μ Module (power module) regulator. Included in the package are the switching controller, power FETs, inductor and compensation components. Operating over an input voltage range from 4.5V to 20V, the LTM4637 supports an output voltage range of 0.6V to 5.5V, set by a single external resistor. Only a few input and output capacitors are needed.

Current mode operation allows precision current sharing of up to four LTM4637 regulators to obtain up to 80A output. High switching frequency and a current mode architecture enable a very fast transient response to line and load changes without sacrificing stability. The device supports frequency synchronization, multiphase/current sharing, Burst Mode operation and output voltage tracking for supply rail sequencing. A diode-connected PNP transistor is available for use as an internal temperature monitor.

The LTM4637 is offered in 15mm × 15mm × 4.32mm LGA and 15mm × 15mm × 4.92mm packages. The LTM4637 is available with SnPb (BGA) or RoHS compliant terminal finish. The LTM4637 is pin compatible with the LTM4627, a 15A DC/DC μ Module regulator.

Features

Application

r catures	Application			
Complete 20A Switch Mode Power Supply	Telecom Servers and Networking Equipment			
4.5V to 20V Input Voltage Range	Industrial Equipment			
0.6V to 5.5V Output Voltage Range	Medical Systems			
Differential Remote Sense Amplifier for Precision Regulation for (VOUT \leq 3.3V)	High Ambient Temperature Systems			
Current Mode Control/Fast Transient Response				
Parallel Current Sharing (Up to 80A)				
Frequency Synchronization				
Selectable Pulse-Skipping or Burst Mode® Operation				
Soft-Start/Voltage Tracking				
Up to 88% Efficiency (12VIN, 1.8VOUT)				
Overcurrent Foldback Protection				
Output Overvoltage Protection				
Internal Temperature Monitor				
Overtemperature Protection				
$15 mm \times 15 mm \times 4.32 mm$ LGA and $15 mm \times 15 mm \times 4.92 mm$ BGA Packages				

SnPb (BGA) or RoHS Compliant (LGA and BGA) Finish

Related Products



LT3763EFE

Analog Devices, Inc TSSOP28



LTC4417IUF Analog Devices, Inc



QFN-24

LTC1966CMS8#PBF

Analog Devices, Inc MSOP-8P







LT1038CK

Analog Devices, Inc TO-3

LTC3440EMS

Analog Devices, Inc MSOP10

LTC2990IMS#PBF

Analog Devices, Inc 10MSOP



LTM8045EY#PBF

Analog Devices, Inc BGA40



LT4295IUFD#PBF

Analog Devices, Inc 28-WFQFN