

LTM4651EY#PBF

Data Sheet

EN55022B Compliant 58V, 24W Inverting-Output DC/DC $\mu Module$ Regulator

| Manufacturers | Analog Devices, Inc | |
|---------------|-----------------------------------|-------------------------------|
| Package/Case | 77-Lead BGA (9mm x 15mm x 5.01mm) | |
| Product Type | Power Management ICs | |
| RoHS | | |
| Lifecycle | | Images are for reference only |
| | | |

Please submit RFQ for LTM4651EY#PBF or Email to us: sales@ovaga.com We will contact you in 12 hours.

<u>RFQ</u>

General Description

The LTM4651 is an ultralow noise, 58V, 24W DC/DC μ Module® inverting topology regulator. It regulates a negative output voltage (VOUT–) from a positive input supply voltage (VIN), and is designed to meet the radiated emissions requirements of EN55022. Conducted emission requirements can be met by adding standard filter components.

Included in the package are the switching controller, power MOSFETs, inductor, filters and support components. The LTM4651 can regulate VOUT- to a value between -0.5V and -26.5V, provided that its input and output voltages adhere to the safe operating area criteria of the LTM4651: VIN + $|VOUT-| \le 58V$. A switching frequency range of 250kHz to 3MHz is supported (400kHz default) and the module can synchronize to an external clock.

Despite being an inverting topology regulator, no level shift circuitry is needed to interface to the LTM4651's RUN, PGOOD or CLKIN pins; those pins are referenced to GND.

The LTM4651 is offered in a 15mm × 9mm × 5.01mm BGA package with SnPb or RoHS compliant terminal finish.

Features

Complete Low EMI Switch Mode Power Supply

EN55022 Class B Compliant

Wide Input Voltage Range: 3.6V to 58V

Up to 4A Output Current

24W Output from 12VIN to -24VOUT, $= 60^{\circ}$ C,>

Output Voltage Range: $-26.5V \le VOUT - \le -0.5V$

Safe Operating Area: VIN + $|VOUT-| \le 58V$

Parallel and Current Share with Multiple LTM4651s

Constant-Frequency Current Mode Control

Frequency Synchronization Range: 250kHz to 3MHz

Power Good Indicator and Programmable Soft-Start

Overcurrent/Overvoltage/Overtemperature Protection

 $15mm \times 9mm \times 5.01mm \, BGA \, Package$

Related Products



Analog Devices, Inc TSSOP28

LT3763EFE



LTC4417IUF Analog Devices, Inc QFN-24







MSOP-8P

Analog Devices, Inc BGA40

Application

Avionics, Industrial Control and Test Equipment


Video, Imaging and Instrumentation

48V Telecom and Network Power Supplies

RF Systems



2 ovaga



LT1038CK

LTC3440EMS

Analog Devices, Inc MSOP10

LTC2990IMS#PBF

Analog Devices, Inc 10MSOP

LT4295IUFD#PBF

Analog Devices, Inc 28-WFQFN