

LTM8047MPY#PBF

Data Sheet

LTM8047MPY#PBF Isolated DC-DC Converter

Manufacturers Analog Devices, Inc

Package/Case BGA45

Product Type Power Management ICs

RoHS

Lifecycle



Images are for reference only

Please submit RFQ for LTM8047MPY#PBF or Final to us; sales@ovaga.com We will contact you in 12 hours.

RFO

General Description

The LTM8047 is an isolated flyback μ Module DC/DC converter. The LTM8047 has an isolation rating of 725VDC. For a similar product with LDO post regulator, see the LTM8048. Included in the package are the switching controller, power switches, transformer, and all support components. Operating over an input voltage range of 3.1V to 32V, the LTM8047 supports an output voltage range of 2.5V to 12V, set by a single resistor. Only output, input, and bypass capacitors are needed to finish the design. Other components may be used to control the soft-start control and biasing.

The LTM8047 is packaged in a thermally enhanced, compact (11.25mm \times 9mm \times 4.92mm) over-molded ball grid array (BGA) package suitable for automated assembly by standard surface mount equipment. The LTM8047 is available with SnPb (BGA) or RoHS compliant terminal finish.

Features

Complete Switch Mode Power Supply

725VDC Isolation

Wide Input Voltage Range: 3.1V to 32V

Up to 440mA Output Current>

2.5V to 12V Output Voltage

Current Mode Control

Programmable Soft-Start

User Configurable Undervoltage Lockout

SnPb or RoHS Compliant Finish

Low Profile (11.25mm × 9mm × 4.92mm) Surface Mount BGA Package

Related Products



LT3763EFE

Analog Devices, Inc TSSOP28



LTC4417IUF

Analog Devices, Inc QFN-24



LTC1966CMS8#PBF

Analog Devices, Inc MSOP-8P



LTM8045EY#PBF

Analog Devices, Inc BGA40



Industrial Sensors

Industrial Switches

Ground Loop Mitigation



LT1038CK

Analog Devices, Inc TO-3



LTC3440EMS

Analog Devices, Inc MSOP10



LTC2990IMS#PBF

Analog Devices, Inc 10MSOP



LT4295IUFD#PBF

Analog Devices, Inc 28-WFQFN