

MC14052BDTR2G

Data Sheet

Analog Multiplexers/Demultiplexers; Package: TSSOP-16; No of Pins: 16; Container: Tape and Reel; Qty per Container: 2500, Multiplexer Switch ICs 3-18V DP4T Analog Sw -55 to 125 deg C

Manufacturers ON Semiconductor, LLC

Package/Case TSSOP-16

Product Type Interface ICs

RoHS Rohs

Lifecycle



Images are for reference only

Please submit RFQ for MC14052BDTR2G or Email to us: sales@ovaga.com We will contact you in 12 hours.

<u>RFQ</u>

General Description

The MC14051B, MC14052B, and MC14053B analog multiplexers are digitally-controlled analog switches. The MC14051B effectively implements an SP8T solid state switch, the MC14052B a DP4T, and the MC14053B a Triple SPDT. All three devices feature low ON impedance and very low OFF leakage current. Control of analog signals up to the complete supply voltage range can be achieved.

Features Application

Triple Diode Protection on Control Inputs

ONSEMI

Switch Function is Break Before Make

Supply Voltage>

Analog Voltage Range (VDD ->

Linearized Transfer Characteristics

Low-noise - 12 nV/sqrt.Cycle,>

Pin-for-Pin Replacement for CD4051, CD4052, and CD4053

For 4PDT Switch, See MC14551B

For Lower RON, Use the HC4051, HC4052, or HC4053 High-Speed CMOS Devices

Pb-Free Packages are Available*

Related Products



MC14051BDR2G

ON Semiconductor, LLC SOIC-16



MC74HC4052ADG

ON Semiconductor, LLC SOIC-16



MC74LVX4051MNTWG

ON Semiconductor, LLC QFN16



MC14067BDWR2G

ON Semiconductor, LLC SOIC-24



MC10EP89DTR2G

ON Semiconductor, LLC TSSOP-8



MC74HC4051ADWR2G

ON Semiconductor, LLC SOIC-16



MC74HC4051ADR2G

ON Semiconductor, LLC SOIC-16



MC14052BDR2G

ON Semiconductor, LLC SOIC-16