


IC REG BUCK ADJUSTABLE 2A 16MSOP

Manufacturers	<a href="#">Analog Devices, Inc</a>
Package/Case	MSOP-16P
Product Type	Power Management ICs
RoHS	
Lifecycle	



Images are for reference only

Please submit RFQ for LT8620IMSE#TRPBF or [Email to us: sales@ovaga.com](mailto:sales@ovaga.com) We will contact you in 12 hours.

[RFQ](#)

## General Description

The LT8620 is a compact, high efficiency, high speed synchronous monolithic step-down switching regulator that accepts a wide input voltage range up to 65V, and consumes only 2.5 $\mu$ A of quiescent current. Top and bottom power switches are included with all necessary circuitry to minimize the need for external components. Low ripple Burst Mode operation enables high efficiency down to very low output currents while keeping the output ripple below 10mVP-P. A SYNC pin allows synchronization to an external clock. Internal compensation with peak current mode topology allows the use of small inductors and results in fast transient response and good loop stability. The EN/UV pin has an accurate 1V threshold and can be used to program VIN undervoltage lockout or to shut down the LT8620 reducing the input supply current to 1 $\mu$ A. A capacitor on the TR/SS pin programs the output voltage ramp rate during start-up. The PG flag signals when VOUT is within  $\pm 9\%$  of the programmed output voltage as well as fault conditions. The LT8620 is available in small 16-Lead MSOP and 3mm  $\times$  5mm QFN packages with exposed pads for low thermal resistance.

## Features

Wide Input Voltage Range: 3.4V to 65V

Ultralow Quiescent Current Burst Mode® Operation:

2.5µA IQ Regulating 12VIN to 3.3VOUT

High Efficiency Synchronous Operation:

94% Efficiency at 1A, 12VIN to 5VOUT

92% Efficiency at 1A, 12VIN to 3.3VOUT

Fast 30ns Minimum Switch-On Time

Low Dropout Under All Conditions: 250mV at 1A

Safely Tolerates Inductor Saturation in Overload

Low EMI

Adjustable and Synchronizable: 200kHz to 2.2MHz

Accurate 1V Enable Pin Threshold

Internal Compensation

Output Soft-Start and Tracking

Small Thermally Enhanced 16-Lead MSOP and 24-Lead 3mm × 5mm QFN Packages

## Application

Automotive and Industrial Supplies

General Purpose Step-Down

GSM Power Supplies

## Related Products



### [LT3763EFE](#)

Analog Devices, Inc  
TSSOP28



### [LT1038CK](#)

Analog Devices, Inc  
TO-3



### [LTC4417IUF](#)

Analog Devices, Inc  
QFN-24



### [LTC3440EMS](#)

Analog Devices, Inc  
MSOP10



### [LTC1966CMS8#PBF](#)

Analog Devices, Inc  
MSOP-8P



### [LTC2990IMS#PBF](#)

Analog Devices, Inc  
10MSOP



[LTM8045EY#PBF](#)

Analog Devices, Inc

BGA40



[LT4295IUFD#PBF](#)

Analog Devices, Inc

28-WFQFN