

LTC2854CDD#TRPBF

Data Sheet

3.3V 20Mbps RS485/RS422 Transceiver with Integrated Switchable Termination; Package: DFN; No of Pins: 10; Temperature Range: 0°C to +70°C

Manufacturers

Analog Devices, Inc

Package/Case

QFN10

Product Type

Interface ICs

RoHS

Pb-free Halide free



Images are for reference only

Please submit RFQ for LTC2854CDD#TRPBF or Email to us: sales@ovaga.com We will contact you in 12 hours.

RFO

General Description

Lifecycle

The LTC2854 and LTC2855 are low power, 20Mbps RS485/RS422 transceivers operating on 3.3V supplies. The receiver includes a logic-selectable 120Ω termination, one-eighth unit load supporting up to 256 nodes per bus (C-, I-Grade), and a fail-safe feature that guarantees a high output state under conditions of floating or shorted inputs.

The driver maintains a high output impedance over the entire common mode range when disabled or when the supply is removed. Excessive power dissipation caused by bus contention or a fault is prevented by current limiting all outputs and by a thermal shutdown.

Enhanced ESD protection allows the LTC2854 to withstand $\pm 25 \text{kV}$ (human body model) and the LTC2855 to withstand $\pm 15 \text{kV}$ on the transceiver interface pins without latchup or damage.

Part NumberDuplexPackageLTC2854HalfDFN-10LTC2855 FullSSOP-16, DFN-12

Features

Integrated, Logic-Selectable 120Ω Termination Resistor

3.3V Supply Voltage

20Mbps Maximum Data Rate

No Damage or Latchup Up to $\pm 25 kV HBM$

High Input Impedance Supports 256 Nodes (C-, I-Grade)

Operation Up to 125°C (H-Grade)

Guaranteed Fail-safe Receiver Operation Over the Entire Common Mode Range

Current Limited Drivers and Thermal Shutdown

Delayed Micropower Shutdown: 5µA Maximum (C-, I-Grade)

Power Up/Down Glitch-Free Driver Outputs

Low Operating Current: 370µA Typical in Receive Mode

Compatible with TIA/EIA-485-A Specifications

Available in 10-Pin 3mm × 3mm DFN, 12-Pin 4mm × 3mm DFN and 16-Pin SSOP Packages

Related Products



LTC4300A-1IMS8#PBF

Analog Devices, Inc MSOP8



LTC2870IFE#PBF

Analog Devices, Inc TSSOP28




LTC6820HMS#PBF

Analog Devices, Inc MSOP-16



LTC2854HDD#PBF

Analog Devices, Inc OFN-10



Low Power RS485/RS422 Transceiver

Level Translator

Backplane Transceiver



LTC2870IUFD#PBF

Analog Devices, Inc 28-QFN



LTC6820IMS#PBF

Analog Devices, Inc MSOP16



LTM2881IV-3#PBF

Analog Devices, Inc LGA32



LTC2852IDD#PBF

Analog Devices, Inc

DFN10