

MAX202EESE

Data Sheet

Line Transmitter/Receiver 2TR 2TX 2RX 16-Pin SOIC N

Manufacturers Analog Devices, Inc

Package/Case SOP-16

Product Type Interface ICs

RoHS

Lifecycle



Images are for reference only

Please submit RFQ for MAX202EESE or Email to us: sales@ovaga.com We will contact you in 12 hours.

RFO

General Description

MAX202EESE is a line driver and receiver integrated circuit (IC) designed to operate in harsh environments. It is produced by Maxim Integrated, and it belongs to the MAX202 series.

Features

Operates on a single +5V power supply

Has two RS-232 drivers and two RS-232 receivers

Supports data rates up to 120kbps

Compliant with EIA/TIA-232E and CCITT V.28 standards

Offers ESD protection of up to $\pm 15 kV$

Available in SOIC and QSOP packages

Application

Industrial automation

Point-of-sale (POS) systems

Networking equipment

Instrumentation and measurement devices

Medical equipment



Related Products



MAX3232EEUE

Analog Devices, Inc TSSOP-16



MAX202CSE

Analog Devices, Inc SOP-16



MAX3221EEUE

Analog Devices, Inc TSSOP-16



MAX490MJA



Analog Devices, Inc CDIP-8



MAX4544EUT+T

Analog Devices, Inc SOT-23-6



MAX485ECPA

Analog Devices, Inc DIP-8



MAX3323EEUE

Analog Devices, Inc TSSOP-16



MAX3232EUE

Analog Devices, Inc TSSOP-16